



## IS2117-1103

ISP Case

Shifting loose cargo can slow down your ops and threaten the mission with damaged freight. The new ISP Case from Pelican™ virtually eliminates load movement with a unique Inter-Stacking Pattern (ISP). The patent pending system is compatible across 6 different case sizes from 4 to 25 cubic feet of storage. Equipped with a silicone sponge O-ring and pressure release valves, the ISP Case is impervious to extreme weather and wet conditions.

The system is designed to maximize the volume of standard logistics platforms. Whether loading standard pallets, NATO pallets, JMIC containers, 463L pallets or sea containers, the ISP Case system will make the most efficient use of cargo space.

With its Inter-Stacking Pattern there is no question where the next case belongs. The disc pattern bottom mates with the wave pattern on the case below, literally falling and locking into place. Cross-stacking builds incredibly tight loads that can save time with strapping or netting.



## CONFIGURATIONS



**IS2117-1103**  
Standard



**IS2117-1103-No-Foam**  
No Foam

## DIMENSIONS

|                         |  |
|-------------------------|--|
| <b>Interior (LxWxD)</b> | 21.00 x 17.00" x 14.00 (53.3 x 43.2 x 35.6 cm) |
| <b>Exterior (LxWxD)</b> | 24.00 x 20.00" x 16.00 (61 x 50.8 x 40.6 cm)   |
| <b>Lid Depth</b>        | 3.00" (7.6 cm)                                 |
| <b>Bottom Depth</b>     | 11.00" (27.9 cm)                               |
| <b>Total Depth</b>      | 14" (35.6 cm)                                  |
| <b>Int Volume</b>       | 2.89 ft <sup>3</sup> (0.082 m <sup>3</sup> )   |

## MATERIALS

|                   |                             |
|-------------------|-----------------------------|
| <b>Body</b>       | RotoMolded Polyethylene     |
| <b>Latch</b>      | Steel (Nickel-black Plated) |
| <b>O-Ring</b>     | Silicone Sponge             |
| <b>Pins</b>       | Stainless Steel             |
| <b>Pins (Alt)</b> | Aluminum                    |
| <b>Purge Body</b> | Aluminum                    |

## COLORS

---

■ Black - 032 Fed Std  
27040

■ Olive Drab - 137 Fed  
Std 34096

■ Gray - 133 Fed Std  
26270

■ Tan - 250 Fed Std  
20372

■ Red - 130 Fed Std  
21105

## WEIGHT

---

**Weight With Foam** 26.00 lbs (11.8 kg)

**Weight Empty** 20.00 lbs (9.1 kg)

## TEMPERATURE

---

**Minimum Temperature** -20°F (-28.9 °C)

**Maximum Temperature** 140°F (60 °C)

## CERTIFICATIONS

---

**MIL-STD-810F**

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 06-07-22*