



1730

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- 5-piece foam set
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open Double Throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Optional Humidity gauge changes color above 40%
- Optional Manual Pressure Equalization Valve
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1730
Standard



1730NF
No Foam



1730WF
With Foam

DIMENSIONS

| | |
|------------------------------|--|
| Interior (LxWxD) | 34.00 x 24.00" x 12.50 (86.4 x 61 x 31.8 cm) |
| Exterior (LxWxD) | 37.50 x 27.13" x 14.37 (95.3 x 68.9 x 36.5 cm) |
| Lid Depth | 2.50" (6.4 cm) |
| Bottom Depth | 10.00" (25.4 cm) |
| Total Depth | 12.5" (31.8 cm) |
| Int Volume | 5.9 ft ³ (0.167 m ³) |
| Padlock Hole Diameter | 5/16" (8 mm) |

MATERIALS

| | |
|---------------|-----------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |

| | |
|-------------------|--------------------------------|
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

| | | |
|---|--|--|
|  Black |  Desert Tan |  OD Green |
|---|--|--|

WEIGHT

| | |
|---------------------------|-----------------------|
| Weight With Foam | 38.00 lbs (17.2 kg) |
| Weight Empty | 30.00 lbs (13.6 kg) |
| Buoyancy | 416.00 lbs (188.7 kg) |
| Master Pack Weight | 43.00 lbs (19.5 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67

OTHER

| | |
|--------------------|-----|
| Wheels | 2 |
| Master Pack | 1 |
| Nameplate | yes |

ACCESSORIES



1731
5 pc. Replacement Foam Set



1733
Replacement O-ring



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



PL2
Padlock (2 pack)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 03-09-21