



2315

The hazard horizon is bright. With Class I, II, III - Division 1 and IECEx ia Safety Certification, 115 lumens and 75 meters of spot beam distance, the Pelican™ 2315 flashlight stretches light across dark, hazardous environments without being a source of ignition.

Engineered with an aluminum core and ABS overmolded plastic, these flashlights are built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

Pelican™ 2315 - SEE THE LIGHT AT THE END OF THE TUNNEL

- Built Pelican tough
- 2 AA Batteries (included)
- Integrated Clip
- Full / Momentary Activation Tail Switch
- Class I, II, III - Division 1 / IECEx ia Safety Certified
- IPX8 1m waterproof
- Helmet mount (included)




DIMENSIONS

| | |
|---------------|-----------------|
| Length | 6.22" (15.8 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|----------------|
| Body | ABS |
| O-Ring | Silicon rubber |
| Lens | PC |
| Shroud | ABS |
| Clip | ABS |

COLORS

| |
|--|
|  High Visibility Yellow |
|--|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|---------------------------|----------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 2 |
| Batteries Included | yes |
| Volts | 3.0v |

WEIGHT






| | |
|---------------------------------|-----------------|
| Weight With Batteries | 4.6 oz (130 gr) |
| Weight Without Batteries | 2.8 oz (79 gr) |

SWITCH

Switch Type Momentary Push Button
Light Modes High

CERTIFICATIONS

Class I, Division 1
Class II, Division 1
Class III, Division 1
IECEX ia

| FL1 STANDARD | HIGH |
|---|---------------|
|  | 115 LUMENS |
|  | 6h 0mins |
|  | 75m |
|  | 1403cd |
|  | IPX8 (1m) |

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 03-09-21