



3410MCC

Right Angle Light

When you can't see the difference between one color cable from another, the job may be compromised. Now you can trust our select flashlights with new Correct Color technology to stop the guess work.

Common LED lights can produce an intense beam and lower CRI (Color Rendering Index), making it difficult to distinguish between different color cables and overpower your work area with blinding bright light. Our new Correct Color flashlights are engineered with a higher CRI(90+ Color Rendering Index) allowing you to see color more accurately in your work environment. And with a low temperature beam (similar to incandescent flashlights) you get the benefits of our Correct Color technology that doesn't outshine the details.

- 3 Modes: High / Medium / Low
- 3 AA Alkaline Batteries (not included)
- Up to 155m Beam Distance
- Up to 484 Lumens
- Learn more about Correct Color Lights



DIMENSIONS

Length	7.44" (18.9 cm)
---------------	-----------------

MATERIALS

Body	Photo luminescent Polycarbonate (PC)
O-Ring	NBR
Lens	Clear Polycarbonate (PC)
Shroud	Photo luminescent Polycarbonate (PC)
Clip	Photo luminescent Polycarbonate (PC)
Contact Spring Retainer	Stainless Steel / Phosphore Bronze / Brass Nickel Plate

COLORS

 Photoluminescent

LIGHT SPECS

Lamp Type	LED
Lamp Secondary Type	LED

POWER






Battery Size	AA
Battery Type	Alkaline
Battery Quantity	3
Volts	4.5v

WEIGHT

Weight With Batteries	9.2 oz (261 gr)
Weight Without Batteries	6.6 oz (187 gr)

SWITCH

Switch Type Push Button
Light Modes High / Medium / Low / Flashing

FL1 STANDARD	MAIN HIGH	MAIN MED	MAIN LOW
	484 LUMENS	64 LUMENS	17 LUMENS
	4h 0mins	20h 0mins	67h 0mins
	155m	56m	29m
	5991cd	796cd	205cd
	IPX8 (1m)		

ACCESSORIES



2469P
Replacement Battery

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 03-09-21